

Round Caulk Bead Chart

REFERENCE ESTIMATE GUIDE

GALLONS OF MIXTURE TO PRODUCE A ROUND CAULK BEAD

*LENGTH OF BEAD IN FEET AND % OF A GALLON

SYSTEM	*	#1	*	#1	*	#1	*	#1	*	#1
BEAD SIZE INCHES	25 FT		50 FT		100 FT		500 FT		1000 FT	
1/8	0.016	1.28	0.03	2.47	0.1	6.74	0.3	24.78	0.6	49.56
1/4	0.064	3.42	0.13	6.93	0.3	15.66	1.3	69.38	2.5	134.30
3/8	0.143	6.95	0.29	14.07	0.6	29.04	2.9	140.74	5.7	277.02
1/2	0.255	11.94	0.51	23.89	1.0	46.88	5.1	238.86	10.2	477.72
5/8	0.398	18.32	0.8	36.82	1.6	73.64	8.0	368.20	15.9	731.94
3/4	0.573	26.13	1.1	50.20	2.3	104.86	11.5	535.70	22.9	1066.94
7/8	0.781	35.40	1.6	72.50	3.1	142.82	15.6	718.56	31.2	1437.12
1	1.019	46.59	2.0	91.48	4.1	187.42	20.4	932.64	40.8	1865.28
1 1/4	1.6	72.50	3.2	145.64	6.4	290.00	31.9	1445.54	63.7	2886.62
1 3/8	1.9	85.88	3.9	176.22	7.7	347.98	38.5	1739.90	77.1	3484.26
1 1/2	2.3	103.72	4.6	207.44	9.2	414.88	45.9	2069.94	91.8	4139.88

PRODUCT COST PER LINEAL FOOT FOR SYSTEM

SYSTEM # 1 – PRIMER APPLICATION OF DURA-FLEX AND A MIXED PRODUCT RATIO OF TWO PARTS DURA-LASTIC / ONE PART DURA-LASTIC THICKENER.

Primer application cost calculation is based upon 1" wide up to 5/8". From 3/4" to 1 1/2" primer application cost calculation is based upon 2" of primer.